

Pure Gigabit Converters

1000Base-T to 1000Base-SX/LX

PART NUMBER	DESCRIPTION
GEP-5001TF-C	(1) RJ-45, 1000Base-T (1) Dual SC, 1000Base-SX (MM/220/500m)
GEP-5101TF-C	(1) RJ-45, 1000Base-T (1) Dual SC, 1000Base-LX (SM/10km)

Specifications

Standards:

IEEE 802.3 1000Base-T Gigabit Ethernet
IEEE 802.3 1000Base-SX/LX Gigabit Ethernet

Interface:

(1) 1000Base-T, Shielded RJ-45 Jack
(1) 1000Base-SX/LX, Dual SC connector

Fiber Wavelength:

850nm (MM), 1310nm (SM)

Link Distance:

1000Base-T: Cat. 5e or 6: up to 100m.
1000Base-SX: Multi-mode fiber 50/125 μ m (500m)
62.5/125 μ m (220m)
1000Base-LX: Single Mode fiber 9/125 μ m (10km)

LED Indicators:

Device: Power
UTP: 1000Mbps, Full-Duplex/collision, Link/Activity
Fiber: Link

DIP Switch:

ON/OFF for UTP Auto Negotiation, Fiber Duplexing,

Power Supply:

External power adapter 9V DC/700mA (min.)

Operating Temperature:

0°C to 45°C (32°-113°F)

Operating Humidity:

10% - 90% RH

EMI:

FCC Class A, CE Mark

Enclosure:

Metal

Dimensions:

4.72"(L) x 3.36"(W) x .96"(H)
118mm x 84mm x 24mm

Warranty:

Limited Lifetime



908 Canada Court
City of Industry, CA 91748 U.S.A.
Phone: 626.964.7873 or 800.346.6668 Fax: 626.964.7880
www.unicomlink.com e-mail: info@unicomlink.com

©UNICOM 2007. UNICOM is a trademark of UNICOM Electric, Inc. All rights reserved.
Specifications subject to change without notice.